

## MTGA 5-8 Metre Linear Actuator mast

Our MM-08035- LA linear actuator mast has a headload of up to 35kg and stands at 5 or 8 metres to the top of the mast and up to 10m to the top of the headstock. It offers smooth deployment and retraction with compact stowage and can withstand wind speeds of up to 100km/h with a 0.8m<sup>2</sup> sail area. Powder-coated for weather protection, in a high visibility orange.

This mast attaches easily via 4 bolts to any deployment requirement and can mount to any equipment. UV protected conduit also protects all cables running up the mast.

The MM-08035-LA linear actuator mast is powered via 12V DC and has one (5m mast) or two (8m mast) linear actuators. The headstock is accessible from the ground allowing the user to access all mounted communications equipment easily. The mast allows for easy and safe extension of the headstock from the ground without the need to access the unit it is installed on or use a safety step. The headstock of the mast always remains vertical with an electric rotational headstock optional for alignment while the mast has been deployed.

Specifications	
Headload	35Kg
Height	5-8 metre
Weight	140kg
Wind speed	100km/h
Colour	Orange (Other colours are available on request)
DC Input	12V
DC Current	17A
Sail Area	0.8m <sup>2</sup>
Mast type	Linear actuator
Material	Mild Steel

